

# A600

# **Fingerprint Scanner**

- ✓ FBI Certified: PIV Specification, Mobile ID FAP 20
- ✓ STQC Certified: UIDAI Level-0 certification
- ✓ Live Finger Detection (LFD)
- ✓ AES-256 Encryption



The Aratek A600 fingerprint scanner is equipped with FBI FAP 20 and STQC certified optical sensor that guarantee you the high quality and usability. Its Live Finger Detection (LFD) and AES-256 Encryption features also allow secure and accurate fingerprint recognition, making it ideal for a wide number of applications across different industries such as national ID, law enforcement, border security, finance, and healthcare etc.

#### **Features**

FBI Certified

PIV Specification, Mobile ID FAP 20

STQC Certified (Non-encrypted version)

UIDAI Level-0 certification

International Standard
ISO19794-2, ISO19794-4, ANSI 378, ANSI 381
and WSQ supported

Live Finger Detection (LFD)

LFD rejects spoofing attempts by screening the liveness of the finger being captured

Advanced Algorithm

NIST MINEX III compliance Bione® fingerprint algorithm delivers the highest extracting and matching performance

AES-256 Encryption (Option)

256-bit AES encryption (AES-256) to ensure the security of your fingerprint data in transit

Correction and Authentication

Support auto correction and 360 degree rotation authentication

Cloud Platform

Seamlessly join in Aratek TrustLink™ biometrics authentication platform

Different OS Support

Windows 2000, XP, Vista, Windows 7 / 8 / 10, Android and other embedded systems

Comprehensive SDK

Comprehensive software development kit is available for development and integration

High Image Quality

Optical fingerprint technology with superior image quality

### **Applications**

- PC/Network Security
- Hospitality
- Finance and Banking

- Telecommunication
- Healthcare
- Law Enforcement

# **A600** Fingerprint Scanner

# **Physical Parameter**

Dimension	98.9*61.5*35.7mm (L*W*H)
	,

#### **Performance Parameter**

Capture Mode	Optical Touch
Platen Size	16.0*21.0 mm
Sensing Area	15.24*20.32 mm
Fingerprint Image Size	300*400 pixels
Image Resolution	500 dpi
Gray level	256 level
Fingerprint Image Distortion	≤1%

#### **Communication Mode**

|--|

# **Operation Environment**

5.0 V (USB)
≤200 mA
0°C-55°C
10-93%R.H
Contact: ±8KV, Air: ±15KV

### Certification

CE, FCC, RoHS, FBI PIV specification, Mobile ID FAP 20, STQC

# **Supported OS**

Windows XP / 7 / 8 / 10, Android, Linux



